



Cable ID: PCF8-10CU-0025-S

Test Limit: ISO11801 Channel Class I

Limits Version: V7.6

Date / Time: 03/07/2023 01:56:59 PM

Operator: QC

Headroom 19.9 dB (NEXT 3,6-4,5)

Cable Type: Cat 8 S/FTP

NVP: 72.0%

Main: Versiv

S/N: 1824298

Software Version: V6.6 Build 2

Calibration Date: 12/02/2022

Adapter: DSX-8000 (DSX-CHA804)

S/N: 22211877

Test Summary: PASS

Remote: Versiv

S/N: 1820302

Software Version: V6.6 Build 2

Calibration Date: 12/02/2022

Adapter: DSX-8000R (DSX-CHA804)

S/N: 22211865

Length (ft)	[Pair 1,2]	1
Prop. Delay (ns), Limit 169	[Pair 1,2]	1
Delay Skew (ns), Limit 16	[Pair 1,2]	0
Resistance (ohms), Limit 6.40	[Pair 1,2]	0.00
Insertion Loss Margin (dB)	[Pair 4,5]	29.8
Frequency (MHz)	[Pair 4,5]	1872.0
Limit (dB)	[Pair 4,5]	31.4

Worst Case Margin Worst Case Value

N/A	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	1,2-3,6	3,6-7,8
NEXT (dB)	22.2	19.9	32.0	33.3
Freq. (MHz)	5.3	3.4	1914.	1920.
Limit (dB)	61.9	65.0	10.3	10.2
Worst Pair	3,6	3,6	3,6	3,6
PS NEXT (dB)	25.0	22.7	32.7	32.4
Freq. (MHz)	5.3	3.4	1914.	1910.
Limit (dB)	58.9	62.0	7.3	7.3

PASS	MAIN	SR	MAIN	SR
Worst Pair	1,2-3,6	3,6-1,2	1,2-3,6	3,6-1,2
ACR-F (dB)	9.7	9.7	9.7	9.7
Freq. (MHz)	1878.	1878.	1878.	1878.
Limit (dB)	6.5	6.5	6.5	6.5
Worst Pair	3,6	3,6	3,6	3,6
PS ACR-F (dB)	10.4	10.6	10.5	10.6
Freq. (MHz)	1864.	1878.	1878.	1878.
Limit (dB)	3.6	3.5	3.5	3.5

N/A	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	1,2-3,6	3,6-7,8
ACR-N (dB)	25.2	22.9	63.9	65.2
Freq. (MHz)	5.3	3.4	1914.	1920.
Limit (dB)	58.9	62.0	-21.6	-21.7
Worst Pair	3,6	3,6	3,6	3,6
PS ACR-N (dB)	28.0	25.7	64.6	64.2
Freq. (MHz)	5.3	3.4	1914.	1910.
Limit (dB)	55.9	59.0	-24.6	-24.5

N/A	MAIN	SR	MAIN	SR
Worst Pair	4,5	4,5	4,5	4,5
RL (dB)	-3.4	-3.9	-1.5	-1.5
Freq. (MHz)	247.5	218.0	669.0	677.0
Limit (dB)	13.5	14.0	9.6	9.5

Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	5GBASE-T
10GBASE-T	25GBASE-T	40GBASE-T
ATM-25	ATM-51	ATM-155
100VG-AnyLan	TR-4	TR-16 Active
TR-16 Passive		

