Lanberg



## SFP1-BIDI-SU-1-20-B

# SFP MODULE SC BIDI 20KM B





## PRODUCT FEATURES:

- Hot pluggable
- DDM

## PRODUCT SPECIFICATION:

| | |
|---|---|
| Maxiumum network link speed | 1 Gbps |
| Network Link Type | Ethernet |
| Specialized | Rack |
| Port | SC / UPC |
| Power consumption (operation) | 1 W |
| Coverage | 20 km |
| Wavelength | 1310 nm, 1550 nm |
| Transmitter Power (Tx Power) | from -9 up to -3 dBm |
| Receiver Sensitivity (Rx Sens.) | -22 dBm |
| Receiver Overload Threshold (Rx Overload) | -3 dBm |
| Functions | DDM |
| Operating temperature | from 0 up to 70 °C |
| Environment temperature | from 0 up to 70 °C |
| Environment humidity | from 5 up to 85 % |

EAN-13: 5901969447842
CAT. NO: SFP1-BIDI-SU-1-20-B

The information contained in this product data sheet corresponds to the product specifications current as of the date of its preparation. The manufacturer may implement design and technological changes in subsequent versions or batches of the product that do not affect the product parameters specified in this data sheet. The current product specifications are available on the manufacturer's website.